






Common Mode Chokes For ADSL and VDSL



-  RoHS peak reflow solder temperature rating 245°C
-  RoHS peak wave solder temperature rating 260°C
-  For use in XDSL interfaces
-  Effective reduction of C.M. noise caused by AM broadcast or ham radio
-  Isolation 1500V line to line

Electrical Specifications @ 25°C - Operating Temperature -40°C to +85°C



RoHS Compliant Part No.	C.M. Attenuation (dB TYP)			Isolation Voltage (Vrms)	Mounting
	@ 500kHz	@ 1kHz	@ 10kHz		
B4001NL	45	49	35	1500	THT
B4003NL	45	49	35	1500	SMT
BX4053NL	45	49	35	150	SM

Notes: Surge Voltage Capability - Metallic: 800Vpeak 10/560sec. Long.: 2400Vpeak 10/700sec. BX4053NL is a dual choke. Please add the suffix "T" for Tape & Reel orders (i.e. B4003NL becomes B4003NLT).

Mechanical

Schematic

B4001NL



Weight2.2grams

Tube60/tube

Dimensions: $\frac{\text{Inches}}{\text{mm}}$



Unless otherwise specified,
all tolerances are $\pm \frac{.010}{0,25}$

Common Mode Chokes For ADSL and VDSL

Mechanicals (continued)

Schematics

B4003NL





Weight1.0grams
Tape & Reel425/reel
Tube50/tube

Dimensions: $\frac{\text{Inches}}{\text{mm}}$

Unless otherwise specified,
all tolerances are $\pm \frac{.010}{0,25}$

BX4053NL



Weight2.1grams
Tape & Reel400/reel
Tube50/tube

Dimensions: $\frac{\text{Inches}}{\text{mm}}$

Unless otherwise specified,
all tolerances are $\pm \frac{.010}{0,25}$

For More Information:

Americas - prodinfonetworkamericas@pulseelectronics.com | Europe - comms-Apps-Europe@pulseelectronics.com | Asia - prodinfonetworkapac@pulseelectronics.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2019. Pulse Electronics, Inc. All rights reserved.